

SIMATIC HMI TP1200 Comfort, Comfort Panel, Touch operation, 12" Widescreen TFT display, 16 million colors, PROFINET interface, MPI/PROFIBUS DP interface, 12 MB configuration memory, Windows CE 6.0, configurable from WinCC Comfort V11



### General information

|                          |                |
|--------------------------|----------------|
| Product type designation | TP1200 Comfort |
|--------------------------|----------------|

### Display

|                   |            |
|-------------------|------------|
| Design of display | TFT        |
| Screen diagonal   | 12.1 in    |
| Display width     | 261.1 mm   |
| Display height    | 163.2 mm   |
| Number of colors  | 16 777 216 |

### Resolution (pixels)

|                               |             |
|-------------------------------|-------------|
| • Horizontal image resolution | 1 280 Pixel |
| • Vertical image resolution   | 800 Pixel   |

### Backlighting

|                                |              |
|--------------------------------|--------------|
| • MTBF backlighting (at 25 °C) | 80 000 h     |
| • Backlight dimmable           | Yes; 0-100 % |

### Control elements

#### Keyboard fonts

|                           |   |
|---------------------------|---|
| • Function keys           |   |
| — Number of function keys | 0 |

|   |                        |
|---|------------------------|
| • Keys with LED   | No                     |
| • System keys   | No                     |
| • Numeric keyboard  | Yes; Onscreen keyboard |
| • alphanumeric keyboard   | Yes; Onscreen keyboard |
| <b>Touch operation</b>  |                        |
| • Design as touch screen  | Yes                    |
| <b>Expansions for operator control of the process</b>                 |                        |
| • DP direct LEDs (LEDs as S7 output I/O)<br>— F1...Fx                 | 0                      |
| • Direct keys (keys as S7 input I/O)<br>— F1...Fx                     | 0                      |
| • Direct keys (touch buttons as S7 input I/O)                         | 40                     |
| <b>Installation type/mounting</b>                                     |                        |
| Mounting position   | vertical               |
| Mounting in portrait format possible                                  | Yes                    |
| Mounting in landscape format possible                                 | Yes                    |
| maximum permissible angle of inclination without external ventilation | 35°                    |
| <b>Supply voltage</b>   |                        |
| Type of supply voltage  | DC                     |
| Rated value (DC)  | 24 V                   |
| permissible range, lower limit (DC)                                   | 19.2 V                 |
| permissible range, upper limit (DC)                                   | 28.8 V                 |
| <b>Input current</b>  |                        |
| Current consumption (rated value)                                     | 0.85 A                 |
| Starting current inrush I <sup>2</sup> t                              | 0.5 A <sup>2</sup> ·s  |
| <b>Power</b>  |                        |
| Active power input, typ.  | 20 W                   |
| <b>Processor</b>  |                        |
| Processor type  | X86                    |
| <b>Memory</b>   |                        |
| Flash   | Yes                    |
| RAM   | Yes                    |
| Memory available for user data  | 12 Mbyte               |
| <b>Type of output</b>   |                        |
| Info LED  | No                     |
| Power LED   | No                     |
| Error LED   | No                     |
| Acoustics   |                        |
| • Buzzer  | No                     |

- Speaker Yes

## Time of day

### Clock

- Hardware clock (real-time) Yes
- Software clock Yes
- retentive Yes; Back-up duration typically 6 weeks
- synchronizable Yes

## Interfaces

|  |                        |
|--|------------------------|
| Number of industrial Ethernet interfaces                       | 1; 2 ports (switch)    |
| Number of RS 485 interfaces                                    | 1; RS 422/485 combined |
| Number of RS 422 interfaces                                    | 0; together with RS485 |
| Number of RS 232 interfaces                                    | 0                      |
| Number of USB interfaces                                       | 2; USB 2.0             |
| <ul style="list-style-type: none"> <li>• USB Mini B</li> </ul> | 1; 5-pole              |
| Number of 20 mA interfaces (TTY)                               | 0                      |
| Number of parallel interfaces                                  | 0                      |
| Number of other interfaces                                     | 0                      |
| Number of SD card slots  | 2                      |
| With software interfaces                                       | No                     |

### Industrial Ethernet

- Industrial Ethernet status LED 2
- Number of ports of the integrated switch 2

## Protocols

|                                   |                      |
|-----------------------------------|----------------------|
| PROFINET                          | Yes                  |
| Supports protocol for PROFINET IO | Yes                  |
| IRT                               | Yes; As of WinCC V12 |
| MRP                               | Yes; As of WinCC V12 |
| PROFIBUS                          | Yes                  |
| MPI                               | Yes                  |

### Protocols (Ethernet)

- TCP/IP Yes
- DHCP Yes
- SNMP Yes
- DCP Yes
- LLDP Yes

### WEB characteristics

- HTTP Yes
- HTTPS Yes
- HTML Yes
- XML Yes
- CSS Yes

|                          |     |
|--------------------------|-----|
| • Active X               | Yes |
| • JavaScript             | Yes |
| • Java VM                | No  |
| <b>Further protocols</b> |     |
| • CAN                    | No  |
| • EtherNet/IP            | Yes |
| • MODBUS                 | Yes |

|   |     |
|---|-----|
| <b>EMC</b>  |     |
| <b>Emission of radio interference acc. to EN 55 011</b> |     |
| • Limit class A, for use in industrial areas            | Yes |
| • Limit class B, for use in residential areas           | No  |

|                                       |      |
|---------------------------------------|------|
| <b>Degree and class of protection</b> |      |
| IP (at the front)                     | IP65 |
| Enclosure Type 4 at the front         | Yes  |
| Enclosure Type 4x at the front        | Yes  |
| IP (rear)                             | IP20 |

|   |     |
|---|-----|
| <b>Standards, approvals, certificates</b> |     |
| CE mark                                   | Yes |
| cULus                                     | Yes |
| RCM (formerly C-TICK)                     | Yes |
| KC approval                               | Yes |

|                                     |                                |
|-------------------------------------|--------------------------------|
| <b>Marine approval</b>              |                                |
| • Germanischer Lloyd (GL)           | Yes; As of product version: 10 |
| • American Bureau of Shipping (ABS) | Yes; As of product version: 10 |
| • Bureau Veritas (BV)               | Yes; As of product version: 10 |
| • Det Norske Veritas (DNV)          | Yes; As of product version: 10 |
| • Lloyds Register of Shipping (LRS) | Yes; As of product version: 10 |
| • Nippon Kaiji Kyokai (Class NK)    | Yes; As of product version: 10 |
| • Polski Rejestr Statkow (PRS)      | No                             |

|                                    |     |
|------------------------------------|-----|
| <b>Use in hazardous areas</b>      |     |
| • ATEX Zone 2                      | Yes |
| • ATEX Zone 22                     | Yes |
| • IECEx Zone 2                     | Yes |
| • IECEx Zone 22                    | Yes |
| • cULus Class I Zone 1             | No  |
| • cULus Class I Zone 2, Division 2 | Yes |
| • FM Class I Division 2            | Yes |

|   |  |
|---|--|
| <b>Ambient conditions</b>                   |  |
| <b>Ambient temperature during operation</b> |  |
| • Operation (vertical installation)         |  |

|  |  |
|--|--|
| — For vertical installation, min.                        | 0 °C                                   |
| — For vertical installation, max.                        | 50 °C; (55 °C, see entry ID: 64847814) |
| • Operation (max. tilt angle)                            |  |
| — At maximum tilt angle, min.                            | 0 °C                                   |
| — At maximum tilt angle, min.                            | 40 °C                                  |
| • Operation (vertical installation, portrait format)     |  |
| — For vertical installation, min.                        | 0 °C                                   |
| — For vertical installation, max.                        | 40 °C                                  |
| • Operation (max. tilt angle, portrait format)           |  |
| — At maximum tilt angle, min.                            | 0 °C                                   |
| — At maximum tilt angle, min.                            | 35 °C                                  |
| <b>Ambient temperature during storage/transportation</b> |  |
| • min.   | -20 °C                                 |
| • max.   | 60 °C                                  |
| <b>Relative humidity</b>                                 |  |
| • Operation, max.  | 90 %; no condensation                  |
| <b>Operating systems</b>                                 |  |
| proprietary  | No                                     |
| <b>pre-installed operating system</b>                    |  |
| • Windows CE   | Yes                                    |
| <b>Configuration</b>                                     |  |
| Message indicator  | Yes                                    |
| Alarm system (incl. buffer and acknowledgment)           | Yes                                    |
| Process value display (output)                           | Yes                                    |
| Process value default (input) possible                   | Yes                                    |
| Recipe management  | Yes                                    |
| <b>Configuration software</b>                            |  |
| • STEP 7 Basic (TIA Portal)                              | No                                     |
| • STEP 7 Professional (TIA Portal)                       | No                                     |
| • WinCC flexible Compact                                 | No                                     |
| • WinCC flexible Standard                                | No                                     |
| • WinCC flexible Advanced                                | No                                     |
| • WinCC Basic (TIA Portal)                               | No                                     |
| • WinCC Comfort (TIA Portal)                             | Yes; from V11                          |
| • WinCC Advanced (TIA Portal)                            | Yes; from V11                          |
| • WinCC Professional (TIA Portal)                        | Yes; from V11                          |
| <b>Languages</b>   |  |
| <b>Online languages</b>                                  |  |
| • Number of online/runtime languages                     | 32                                     |
| <b>Project languages</b>                                 |  |
| • Languages per project                                  | 32                                     |

## Functionality under WinCC (TIA Portal)

|  |         |
|--|---------|
| Libraries  | Yes     |
| Applications/options   |         |
| • Web browser  | Yes     |
| • Pocket Word  | Yes     |
| • Pocket Excel   | Yes     |
| • PDF Viewer   | Yes     |
| • Media Player   | Yes     |
| • SIMATIC WinCC Sm@rtServer                                      | Yes     |
| • SIMATIC WinCC Audit  | Yes     |
| Number of Visual Basic Scripts                                   | Yes     |
| Task planner   |         |
| • time-controlled  | Yes     |
| • task-controlled  | Yes     |
| Help system  |         |
| • Number of characters per info text                             | 70      |
| <b>Message system</b>  |         |
| • Number of alarm classes  | 32      |
| • Bit messages   |         |
| — Number of bit messages   | 4 000   |
| • Analog messages  |         |
| — Number of analog messages                                      | 200     |
| • S7 alarm number procedure                                      | Yes     |
| • System messages HMI  | Yes     |
| • System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.) | Yes     |
| • Number of characters per message                               | 80      |
| • Number of process values per message                           | 8       |
| • Acknowledgment groups  | Yes     |
| • Message indicator  | Yes     |
| • Message buffer   |         |
| — Number of entries  | 1 024   |
| — Circulating buffer   | Yes     |
| — retentive  | Yes     |
| — maintenance-free   | Yes     |
| <b>Recipe management</b>   |         |
| • Number of recipes  | 300     |
| • Data records per recipe  | 500     |
| • Entries per data record  | 1 000   |
| • Size of internal recipe memory                                 | 2 Mbyte |
| • Recipe memory expandable                                       | Yes     |

| Variables                              |       |
|--|-------|
| • Number of variables per device       | 2 048 |
| • Number of variables per screen       | 400   |
| • Limit values                         | Yes   |
| • Multiplexing                         | Yes   |
| • Structures                           | Yes   |
| • Arrays                               | Yes   |
| Images                                 |       |
| • Number of configurable images        | 500   |
| • Permanent window/default             | Yes   |
| • Global image                         | Yes   |
| • Pop-up images                        | Yes   |
| • Slide-in images                      | Yes   |
| • Image selection by PLC               | Yes   |
| • Image number in the PLC              | Yes   |
| Image objects                          |       |
| • Number of objects per image          | 400   |
| • Text fields                          | Yes   |
| • I/O fields                           | Yes   |
| • Graphic I/O fields (graphics list)   | Yes   |
| • Symbolic I/O fields (text list)      | Yes   |
| • Date/time fields                     | Yes   |
| • Switches                             | Yes   |
| • Buttons                              | Yes   |
| • Graphic display                      | Yes   |
| • Icons                                | Yes   |
| • Geometric objects                    | Yes   |
| Complex image objects                  |       |
| • Number of complex objects per screen | 20    |
| • Alarm view                           | Yes   |
| • Trend view                           | Yes   |
| • User view                            | Yes   |
| • Status/control                       | Yes   |
| • Sm@rtClient view                     | Yes   |
| • Recipe view                          | Yes   |
| • f(x) trend view                      | Yes   |
| • System diagnostics view              | Yes   |
| • Media Player                         | Yes   |
| • HTML browser                         | Yes   |
| • PDF display                          | Yes   |
| • IP camera display                    | Yes   |

|  |                |
|--|----------------|
| • Bar graphs                           | Yes            |
| • Sliders                              | Yes            |
| • Pointer instruments                  | Yes            |
| • Analog/digital clock                 | Yes            |
| <b>Lists</b>                           |                |
| • Number of text lists per project     | 500            |
| • Number of entries per text list      | 500            |
| • Number of graphics lists per project | 500            |
| • Number of entries per graphics list  | 500            |
| <b>Archiving</b>                       |                |
| • Number of archives per device        | 50             |
| • Number of entries per archive        | 20 000         |
| • Message archive                      | Yes            |
| • Process value archive                | Yes            |
| • Archiving methods                    |                |
| — Sequential archive                   | Yes            |
| — Short-term archive                   | Yes            |
| • Memory location                      |                |
| — Memory card                          | Yes            |
| — USB memory                           | Yes            |
| — Ethernet                             | Yes            |
| • Data storage format                  |                |
| — CSV                                  | Yes            |
| — TXT                                  | Yes            |
| — RDB                                  | Yes            |
| <b>Security</b>                        |                |
| • Number of user groups                | 50             |
| • Number of user rights                | 32             |
| • Number of users                      | 50             |
| • Password export/import               | Yes            |
| • SIMATIC Logon                        | Yes            |
| <b>Logging through printer</b>         |                |
| • Alarms                               | Yes            |
| • Report (shift log)                   | Yes            |
| • Hardcopy                             | Yes            |
| • Electronic print to file             | Yes; PDF, HTML |
| <b>Character sets</b>                  |                |
| • Keyboard fonts                       |                |
| — US English                           | Yes            |
| <b>Transfer (upload/download)</b>      |                |
| • MPI/PROFIBUS DP                      | Yes            |



|  |                                    |
|--|------------------------------------|
| • USB  | Yes                                |
| • Ethernet   | Yes                                |
| • using external storage medium                          | Yes                                |
| <b>Process coupling</b>                                  |                                    |
| • S7-1200  | Yes                                |
| • S7-1500  | Yes                                |
| • S7-200   | Yes                                |
| • S7-300/400   | Yes                                |
| • LOGO!  | Yes                                |
| • WinAC  | Yes                                |
| • SINUMERIK  | Yes; with SINUMERIK option package |
| • SIMOTION   | Yes                                |
| • Allen Bradley (EtherNet/IP)                            | Yes                                |
| • Allen Bradley (DF1)                                    | Yes                                |
| • Mitsubishi (MC TCP/IP)                                 | Yes                                |
| • Mitsubishi (FX)  | Yes                                |
| • OMRON (FINS TCP)                                       | No                                 |
| • OMRON (LINK/Multilink)                                 | Yes                                |
| • Modicon (Modbus TCP/IP)                                | Yes                                |
| • Modicon (Modbus)                                       | Yes                                |
| • OPC UA Client  | Yes                                |
| • OPC UA Server  | Yes                                |
| <b>Service tools/configuration aids</b>                  |                                    |
| • Backup/Restore manually                                | Yes                                |
| • Backup/Restore automatically                           | Yes                                |
| • Simulation   | Yes                                |
| • Device switchover                                      | Yes                                |
| <b>Peripherals/Options</b>                               |                                    |
| <b>Peripherals</b>                                       |                                    |
| • Printer  | Yes                                |
| • SIMATIC HMI MM memory card: Multi Media Card           | Yes; Up to 128 MB                  |
| • SIMATIC HMI SD memory card: Secure Digital memory card | Yes; Up to 2 GB                    |
| • SIMATIC HMI CF memory card Compact Flash Card          | No                                 |
| • USB memory   | Yes                                |
| • SIMATIC IPC USB Flashdrive (USB stick)                 | Yes; Up to 16 GB                   |
| • SIMATIC HMI USB stick                                  | Yes; Up to 8 GB                    |
| • Network camera   | Yes                                |
| <b>Mechanics/material</b>                                |                                    |

|                            |     |
|----------------------------|-----|
| Enclosure material (front) |     |
| • Plastic                  | No  |
| • Aluminum                 | Yes |
| • Stainless steel          | No  |

### Dimensions

|                            |        |
|----------------------------|--------|
| Width of the housing front | 330 mm |
| Height of housing front    | 241 mm |
| Mounting cutout, width     | 310 mm |
| Mounting cutout, height    | 221 mm |
| Overall depth              | 65 mm  |

### Weights

|                          |        |
|--------------------------|--------|
| Weight without packaging | 2.8 kg |
| Weight incl. packaging   | 3.5 kg |

**last modified:** 12/22/2017