

## Hand-cranked insulation testers

### **C.A 6501 & C.A 6503**

### **IMEG 500N & IMEG 1000N**

*Lightweight and compact, the C.A 6501 and C.A 6503 insulation testers are hand-held instruments which are totally independent because they are powered by a hand-cranked magneto. Particularly versatile, they are ideal for on-site, industrial and residential applications, power distribution networks, telecommunications, etc. They can be used to check that electrical installations comply with the applicable standards, as well as for preventive maintenance on cables, motors, circuit-breakers, etc.*



C.A 6501

C.A 6503



No batteries  
required

### **Ergonomics**

- Simple, immediate implementation
- Lightweight instrument
- Site-proof version with rugged plastic casing suitable for all C.A 6501 & C.A 6503 operating situations
- Reinforced version in a metal case for difficult environments, delivered in a field case (IMEG 500N & IMEG 1000N)

### **Measurement**

- Strictly constant test voltage
- Auto-ranging
- Insulation measurement up to 200 MΩ with the C.A 6501 and up to 500 MΩ with the C.A 6503
- LEDs to indicate when measurement conditions are satisfactory

### **Safety**

- Automatic discharging at the end of the test
- Measurements comply with the NFC 15-100, IEC 60364-6 and VDE 0110 standards, etc

### **Power supply**

- Powered independently by hand-cranked magneto



IMEG 500N / IMEG 1000N

	<b>C.A 6501 IMEG 500N</b>	<b>C.A 6503 IMEG 1000N</b>
<b>Insulation (MΩ calibre)</b>		
Test voltage (DC)	500 V	250 V / 500 V / 1000 V
Range	0.5 to 200 MΩ	1 to 5000 MΩ
Accuracy	2.5 % at full scale	2% at full scale
<b>Resistance</b>		
Range	45 to 500 kΩ	—
Accuracy	2.5% at full scale	—
<b>Continuity</b>		
Range	0 to 100 Ω	—
Accuracy	2% at full scale	—
<b>Voltage</b>		
Range	0 to 600 V <sub>AC</sub>	0 to 600 V <sub>AC</sub>
Frequency	45 to 450 Hz	45 to 450 Hz
Accuracy	3% at full scale	3% at full scale
<b>Other Features</b>		
Display	Analog	Analog
Dimensions	120 x 120 x 130 mm	120 x 120 x 130 mm
Weight	1.06 kg	1.06 kg
Power supply	Hand-cranked magneto: stable, constant test voltage	Hand-cranked magneto: stable, constant test voltage
Protection rating	High protection: IP 54 with cover / IP 52 without	High protection: IP 54 with cover / IP 52 without
Electrical safety	IEC 61010 – 600 V CAT II / 300 V CAT III	IEC 61010 – 600 V CAT II / 300 V CAT III

 : No batteries required

## Ordering information

### > IMEG 500N.....P01132501A

Delivered in on-site case with 1 operating manual, 2 elbowed/straight PVC leads 1.5 m long (black/red), 1 earth lead, 2 crocodile clips (black/red), 1 black test probe.

### > IMEG 1000N.....P01132502A

Delivered in on-site case with 1 operating manual, 3 elbowed/straight PVC leads 1.5 m long (black/red/blue), 1 earth lead, 3 crocodile clips (black/red/blue), 1 black test probe.

### > C.A 6501.....P01132503

Delivered in carrying bag with 1 operating manual, 2 elbowed/straight PVC leads 1.5 m long (black/red), 1 earth lead, 2 crocodile clips (black/red), 1 black test probe.

### > C.A 6503 .....P01132504

Delivered in carrying bag with 1 operating manual, 3 elbowed/straight PVC leads 1.5 m long (black/red/blue), 1 earth lead, 3 crocodile clips (black/red/blue), 1 black test probe.

## Accessories/Replacement parts

C.A 846 thermo-hygrometer.....	P01156301Z
C.A 861 thermometer + K thermocouple.....	P01650101Z
0.2 A fuses (set of 10).....	P02297302
Set of 2 crocodile clips (red/black).....	P01102052Z
Set of 2 test probes (red/black).....	P01102051Z
Set of 2 leads 1.5 m long (red/black).....	P01295283Z
5 crocodile clips (red, black, blue, yellow, green/yellow).....	P01101849
3 safety leads 1.5 m long (red, blue, black).....	P01295171

