theben-timer 26 IP 44

Item no.: 0260855



Time and light control Analogue time switches

Description

- Analogue plug-in timer
- 1 channel
- Without power reserve
- Synchronised with mains
- Use with earthed sockets
- Switching preselection
- Switching status display



Technical data

	theben-timer 26 IP 44
Operating voltage	230 V AC
Frequency	50 Hz
Number of channels	1
Installation type	Plug-in
Type of connection	Plug-in
Program	Daily program
Switching capacity at 250 V AC, $\cos \varphi$ = 1	16 A
Switching capacity at 250 V AC, cos φ = 0,6	4 A
Incandescent/halogen lamp load	3500 W
LED lamp < 2 W	40 W
LED lamp 2-8 W	400 W

	theben-timer 26 IP 44
LED lamp > 8 W	400 W
Shortest switching times	15 min
Programmable every	15 min
Time accuracy at 25 °C	Synchronised with mains
Type of contact	NO contact
Number of switching segments	96
Stand-by consumption	~0.8 W
Housing and insulation material	High-temperature resistant, self- extinguishing thermoplastic
Type of protection	IP 44
Protection class	II according to EN 60 730-1
Ambient temperature	-40°C 55°C

theben-timer 26 IP 44

Item no.: 0260855



Connection example

